

New from Consul

Consul HD4000 & HD4000 Plus

Consul introduce a new all-rounder.

A base frame free 2 post hydraulic lift with 4 tonnes capacity, long triple extension arms and low pad clearance, the lift is ideal for the workshop looking for a cost effective general purpose lift. It can safely lift a range of vehicles from city cars (e.g. VW up, Smart etc.) to many light commercials. The lift is available with an optional height extension to accommodate high roofed vehicles.



Features of the lift include:

- Double S-profile lifting columns provides exceptional rigidity with minimal space requirements. It also decreases the wear in the carriage guides.
- Narrow footprint.
- "Softline" push button controls.
- Automatic arm locking device with manual override.
- Low noise, energy efficient hydraulic pump.
- High pressure cylinder in each post.
- Mechanical safety locks on both carriages, electrical release.
- Synchronization by cables.
- Automatic vehicle roof protection switch.

- 3-part, double extendable telescopic, asymmetric lift arms.
- Foot protection brackets with integrated tool trays included.
- Optional: HD 4000 Plus (Column extension by 500 mm for higher vehicles)
- Protection class IP54, GS-approves, DIN EN 1493, CE-approved, model approved

Modell		HD4000	HD4000 Plus
Artikel-Nr.		58760.0	58185.0
Tragfähigkeit <i>Capacity</i>	kg	4.000	4.000
Motorleistung <i>Motor data</i>	kW / A / V	2,2 / 16 / 400	2,2 / 16 / 400
Hub- / Senkzeit <i>Lifting- / lowering time</i>	s	55 / 30	55 / 30
A Hubhöhe <i>Lifting height</i>	mm	1.915	1.915
B Aufstellhöhe (Querverbindung) <i>Set-up height (cross beam)</i>	mm	3.916 ¹ 3.790 ²	4.416 ¹ 4.290 ²
C Aufstellbreite <i>Set-up width</i>	mm	3.384	3.384
D Durchfahrbreite <i>Drive-through width</i>	mm	2.540	2.540
E Tragarmlänge lang min. <i>Long arm extension min.</i>	mm	750 (3-teilig, 3 pcs.)	750 (3-teilig, 3 pcs.)
F Tragarmlänge lang max. <i>Long arm extension max.</i>	mm	1.330 (3-teilig, 3 pcs.)	1.330 (3-teilig, 3 pcs.)
G Tragarmlänge kurz min. <i>Short extension min.</i>	mm	600 (3-teilig, 3 pcs.)	600 (3-teilig, 3 pcs.)
H Tragarmlänge kurz max. <i>Short arm extension max.</i>	mm	1100 (3-teilig, 3 pcs.)	1.100 (3-teilig, 3 pcs.)
I Unterschwenkhöhe <i>Swivel-in height</i>	mm	90 - 115	90 - 115
J Säulenabstand Innen <i>Clear distance columns</i>	mm	2.760	2.760

